

PRODUCT SPECIFICATION

(產品規格書)

Ordering information

4977-	1X	04	M	H	B
Series	1: 1 Row	02~10	M: Male	H: Housing	B: Bulk Package
		No. of Pin Per Row	F: Female		
	3: 3 Row	02.03.04.05			
		No. of Pin Per Row			

A1:JUL.17/2012.

A2:MAY.14/2013.(端子規格書獨立)

PRODUCT NAME (產品名稱)	DOCUMENT No.: (文件編號)	Rev. (版本)	OUPIIN
6.35mm Wafer	4977spec-H	A2	(歐品)
Housing	Approved (核準)	Checked (審核)	Prepared (製作)
(RoHS)	Q.A. Section Chief	Amy Chiu	MAY.14/2013

1. SCOPE (範圍)	3
2. REFERENCE DOCUMENTS (參考文件)	3
3. FEATURE & DIMENSIONS (特徵及尺寸)	3
3.1. <i>PRODUCT DIMENSION (產品尺寸)</i>	3
3.2. <i>PCB/PANEL LAYOUT (印刷電路板佈局)</i>	3
3.3. <i>BILL OF MATERIAL (材料清單)</i>	3
3.4. <i>MECHANICAL & ELECTRICAL CHARACTERISTIC (機械及電器特性)</i>	3
3.5. <i>PACKAGING (包裝)</i>	3
3.6. <i>RATING CURRENT AND RATING VOLTAGE 額定電流與額定電壓</i>	4
3.7. <i>OPERATING TEMPERATURE 使用溫度</i>	4
4. Environmental (環境要求)	4
4.1. <i>SOLDERABILITY (可焊性)</i>	4
4.2. <i>RESISTANCE TO SOLDER HEAT (耐焊接熱)</i>	4
WAVE SOLDERING (波峰焊)	4
1.Preheat (預熱)	4
2.Soldering (焊接)	4
3.Cool Down (冷卻)	4
5. PERFORMANCE AND TEST DESCRIPTION (性能及測試)	5
5.1. <i>REQUIREMENT (要求)</i>	5
5.2. <i>TEST CONDITION (測試條件)</i>	5
5.3. <i>SAMPLE SELECTION (樣品選擇)</i>	5
Table I: Test Requirements and Procedure	6
(附錄一: 測試要求)	
Table II: Material	7-9
(附錄二: 材料證明)	

1. SCOPE (範圍)

This product specification defines the product performance and the test methods to ascertain the performance of the 6.35mm Housing, which is designed and manufactured by Oupiin Electronic Co.,Ltd.

(本產品規格書規定了由歐品電子有限公司生產的 6.35mm Housing 型連接器,產品的特性及測試方法.)

2. REFERENCE DOCUMENTS (參考文件)

MIL-STD-1344A	Test method for electrical connector (電子連接器測試方法)
MIL-STD-202F	Test method for electrical components (電子零件測試方法)

3. FEATURE & DIMENSIONS (特徵及尺寸)

3.1. PRODUCT DIMENSION (產品尺寸)

These connectors shall have the dimensions as shown in drawing.
(本產品的相關尺寸參考圖面.)

3.2. PCB/PANEL LAYOUT (印刷電路板佈局)

The recommended PCB layout is shown in drawing.
(本產品適用的 PCB layout 參考圖面.)

3.3. BILL OF MATERIAL (材料清單)

Harmful material control follow the requirement of RoHS. The bill of material and product number is described in drawing.
(有害物質控制符合RoHS指令要求.本產品使用的材料參考附件.)

3.4. MECHANICAL & ELECTRICAL CHARACTERISTIC (機械及電氣特性)

The connector shall have the mechanical and electrical performance as described in drawing.
(本產品的機械及電氣特性見圖面：)

3.5. PACKAGING (包裝)

Products shall be packaged according to requirements specified in purchase order for safe delivery, connector container and the packaging method are shown in package specification.
(產品可依客戶指定要求包裝, 包裝材料與包裝方式參見產品包裝規範。)

3.6 RATING CURRENT AND RATING VOLTAGE 額定電流與額定電壓

Rating current is 10 A, rating voltage is 600V DC/AC RMS.

額定電流 10A，額定電壓 600V DC/AC RMS。

3.7 OPERATING TEMPERATURE 使用溫度

Temperature range: -55°C~+105°C.

溫度範圍：-55°C~+105°C。

4. ENVIRONMENTAL (環境要求)

4.1. SOLDERABILITY (可焊性)

Connectors meet solder ability to MIL-STD-202F. Finish shall be free of contaminants.

(產品可焊性符合 MIL-STD-202F 標準規定的相關要求，表面不得有污染物.)

4.2. RESISTANCE TO SOLDER HEAT (耐焊接熱)

WAVE SOLDERING (波峰接)

Each cycle consists of three consecutive phases.

(每個焊接週期包括三個連續的階段)

1. Preheat (預熱)

The steady temperature of the preheat zone is 90~125°C.

(預熱區最終溫度控制在90~125°C)

2. Soldering (焊接)

To avoid the secondary tin-melting, the temperature on PCB upper surface is 160°C Max. for products with lead, or 200°C Max. for lead-free products. The temperature of the PCB bottom surface shall not be exceed 100°C more than the temperature of the PCB upper surface. The peak temperature is during 220~230°C for products with lead, or 230~245°C for lead-free products. The tin dip time is duration for 3~5 seconds.

(有鉛產品板面溫度不得超過160°C，無鉛產品板面溫度不得超過200°C，以防止貼片零件二次熔錫。板面溫度與板底的溫度溫差不得超過100°C。板下溫度峰值有鉛產品維持在220~230°C，無鉛產品控制在230~245°C。浸錫時間控制在3~5秒。)

3. Cool Down (冷卻)

Cool down shall not exceed 6°C per second.

(冷卻速度不超過6°C/秒.)

Note: (說明)

Device temperature measurements are referenced from the top-center of the package outer surface.

(設備溫度量測時以從頂部中間位置測量為準.)

5. PERFORMANCE AND TEST DESCRIPTION

(性能及測試)

5.1. REQUIREMENT (要求)

Product is designed to meet electrical, mechanical, and environmental performance requirements specified in **Table I**.

(本產品設計符合附表一所述的機械，電氣及環境要求。)

5.2. TEST CONDITION (測試條件)

Unless otherwise specified, all tests shall be performed at ambient environmental conditions.

(除非特別注明，所有測試在室溫條件下完成；)

5.3. SAMPLE SELECTION (樣品選擇)

Test samples shall be selected at random from current production. No test samples shall be reused. Samples are pre-conditioned with 10cycles of durability. Each group shall be containing 5 test samples.

(測試樣品從現生產的產品中隨機抽取，所有測試過的樣品不得重複使用。樣品已預先插拔10次，每組測試有5個樣品；)

Table I: Test Requirements and Procedures
(附錄一:測試要求)

Items (項目)	Requirements (要求)	Test Methods (檢測方法)
1. Confirmation of Product (產品確認)	Product shall be conforming to the requirements of applicable product drawing. (產品必須滿足相關檔的規定)	Check the dimensions and functions per applicable product drawing in your eyes. (目視，尺寸及功能依產品圖面檢查)
2. Insulation Resistance (絕緣阻抗)	1000 M Ω Min. (最小)	Measure by applying test potential between the adjacent contacts, and between the contacts and ground in the mated connector. MIL-STD-202, Method 302, Condition B (500 V DC \pm 10%). (測試產品端子間以及端子與接地間的電阻，適用：MIL-STD-202,方法 302，條件 B) (500V DC \pm 10%)
3. Dielectric Strength (耐電壓)	Connector must withstand test potential of 600 V AC for 1 minute. Current leakage must be 0.5 m A max. (樣品必須承受測試電壓 600V AC，時間一分鐘，漏電流不大於 0.5 mA.)	Measure by applying test potential between the adjacent contacts, and between the contacts and ground in the mated connector. MIL-STD-202, Method 301. (測試產品端子間以及端子與接地間的電壓，適用：MIL-STD-202，方法 301。)
4. Solder ability (可焊性)	Appearance of the specimen shall be inspected after the test with the assistance of a magnifier capable of giving a magnification of 10 X for any damage such as pinholes, void or rough surface. (樣品在測試完成後，在放大倍數為 10 倍的顯微鏡下，檢查外觀損壞如：小孔，空焊，外觀粗糙度；)	Soldering time: 3 to 5 Seconds (焊接時間：3~5 秒) Peak Temperature: 245 \pm 5 $^{\circ}$ C. (最高溫度：245 \pm 5 $^{\circ}$ C.)

Material Housing : 016-PA66

[SGS Test Report Click here](#)

[如需 SGS 測試報告請點選此處](#)



TL/0124/1997.289/UK

TECHNYL ? A 205F

Description	Unreinforced polyamide 66 , high fluidity , fast cycling grade, for injection moulding .									
Applications	<p>TECHNYL A 205F offers two main advantages : excellent filling qualities and UL 94 V2 under 0.4 mm.</p> <p>It is particularly suitable for the moulding of long parts with thin wall sections, such as :</p> <ul style="list-style-type: none">- cable ties and fasteners,- connectors. <p>This product is available in natural, black and in colours on request</p>									
Processing	<p>The material is supplied in airtight bags, ready for use . In the case that the virgin material has absorbed moisture, it must be dried to a final moisture content of less than 0,2% with a dehumidified air drying equipment at approx 80°C.</p> <p>Recommended moulding conditions :</p> <table><tr><td>Barrel temperatures :</td><td>- feed zone</td><td>270 - 275°C</td></tr><tr><td></td><td>- compression zone</td><td>280 - 285°C</td></tr><tr><td></td><td>- front zone</td><td>285 - 290°C</td></tr></table> <p>Mould temperatures : 60 at 80°C</p> <p>For more detailed information , please refer to the technical sheet "Injection moulding".</p>	Barrel temperatures :	- feed zone	270 - 275°C		- compression zone	280 - 285°C		- front zone	285 - 290°C
Barrel temperatures :	- feed zone	270 - 275°C								
	- compression zone	280 - 285°C								
	- front zone	285 - 290°C								
Safety	Please refer to the Material Safety Data Sheet A1									

TECHNYL ? A 205F

Main properties

Values measured at 23 °C

The values of properties are for natural grade.

Properties	Standards	Unit	Values	
			EH 0 ? 23 °C	EH 50 ? 23 °C
Physical				
Water absorption, 24h in water at 23°C	ISO 62	%	1.2	-
Density	ISO 1183-A	g/cm ³	1.14	-
Moulding shrinkage longitudinal	RHODIA-EP	%	1.9	-
Moulding shrinkage transverse	RHODIA-EP	%	1.9	-
Mechanical				
Tensile Modulus	ISO 527	MPa	3200	1600
Yield stress	ISO 527	MPa	85	50
Elongation at yield	ISO 527	%	4	10
Tensile strain at break	ISO 527	%	25	200
Stress at 50% elongation	ISO 527	MPa	-	50
Tensile stress at break	ISO 527	MPa	60	40
Flexural modulus	ISO 178	MPa	2900	1300
Flexural strength	ISO 178	MPa	120	50
Charpy notched impact strength	ISO 179(1E)-1993	kJ/m ²	4.5	8
Charpy notched impact strength ISO179/1A	ISO 179-1982	kJ/m ²	5	15
Charpy impact strength	ISO 179(1E)-1993	kJ/m ²	NB	NB
Charpy impact strength ISO 179/1D	ISO 179-1982	kJ/m ²	NB	NB
Izod notched impact strength	ISO 1E3	kJ/m ²	4.5	6
Thermal				
Melt temperature	ISO 3146 - C	°C	263	-
Temper. of dimensional stability 1,8 MPa	ISO 75-2	°C	75	-
Coef. linear expansion longit. 23°C-85°C	ASTM E 431	E-5 / %	7	-
Flammability UL94 thickness 0,4mm	ISO 1210(UL 94)	-	V2	-
Flammability UL94 thickness 0,8mm	ISO 1210(UL 94)	-	V2	-
Flammability UL94 thickness 1,6 mm	ISO 1210(UL 94)	-	V2	-
Glow wire test thickness 1,6 mm	IEC 606-2-1	°C	850	960
Electrical				
Relative permittivity 1MHz	IEC 253	-	2.9	3.2
Dissipation factor 1 MHz	IEC 253	-	0.03	0.08
Volume resistivity	IEC 91	E14.Ohm.cm	10	0.1
Surface resistivity	IEC 91	E14.Ohm	5	0.1
Dielectric strength	IEC 24-1	kV/mm	27	26
Comparative tracking index KC	IEC 112	Volt	600	600
Comparative tracking index KB	IEC 112	Volt	550	-
Specific				
Limit oxygen index	ISO 4509	%	28.5	-

Identification code

>PA66<

The information contained in this document is supplied in good faith. It is based on the extent of our knowledge of the products as listed, and on the tests and experiments carried out in our laboratories. It is to be used only as an indication and shall not be construed in any way as a formal commitment or warranty on our part. Compliance of our products with your conditions of application or use can only be determined pursuant to your own prior appropriate test. The listed values of properties are for natural grade, if not otherwise specified.



Engineering Plastics

Avenue Rambois: BP 64 F-69192 Saint-Fons Cedex. Telephone: +33 (0)4 72 89 27 00 Fax: +33(0)4 72 89 27 01

RHODIA ENGINEERING PLASTICS. Société Anonyme au capital de : 71 256 400 F - 393 335 104 RCS Lyon



PRODUCT SPECIFICATION OF OUPIIN

Material Housing :UL(UL94V-2)

UL iQ for Plastics Yellow Card

第 1 頁 , 共 1 頁



QMFZ2 Component - Plastics

Tuesday, December 13, 2005

E44716

RHODIA ENGINEERING PLASTICS

QUARTIER BELLE-ETOILE AVE RAMBOZ BOITE POSTALE 64 ST FONS CEDEX 69192 FR

Material Designation: **A 205F(r4)**

Product Description: Polyamide 66 (PA66), designated "Technyl" furnished as pellets.

Color	Min. Thick. (mm)	Flame Class	HWI	HAI	RTI Elec	RTI Imp	RTI Str	IEC GWIT	IEC GWFI
ALL	0.38	V-2	4	0	105	-	-	-	-
	0.75	V-2	4	0	110	75	85	-	-
	1.5	V-2	3	0	115	75	85	-	-
	3.0	V-2	2	0	120	75	85	-	-
BK	3.0	V-2	2	0	120	85	95	-	-

CTI: 0 IEC CTI (V): - HVTR: 0 D495: 5 IEC Ball Pressure (°C): -

Dielectric Strength (kV/mm): -

Volume Resistivity (10⁹ohm-cm): -

Dimensional Stability(%): -

ISO Tensile Strength (MPa): -

ISO Flexural Strength (MPa): -

ISO Heat Deflection (°C): -

ISO Tensile Impact (kJ/m²): -

ISO Izod Impact (kJ/m²): -

ISO Charpy Impact (kJ/m²): -

(r4) Virgin and regrind up to 50% by weight inclusive have the same basic material.

NOTE Materials designated "Technyl" may be prefixed by the letters "TY".

Report Date: 9/17/1992

Underwriters Laboratories Inc®

UL94 small-scale test data does not pertain to building materials, furnishings and related contents. UL 94 small-scale test data is intended solely for determining the flammability of plastic materials used in components and parts of end-product devices and appliances, where the acceptability of the combination is determined by ULI.

[http://iq.ul.com/iq/ULiQ_MyLink/card.asp?card\]=235549&\[AskFile\]=E44716&\[AskCompa...](http://iq.ul.com/iq/ULiQ_MyLink/card.asp?card]=235549&[AskFile]=E44716&[AskCompa...) 2006/4/17