






| | | | |
|------|---------------|-----------|-------|
| REV. | SPECIFICATION | ECN NO. | APPD. |
| R2 | | ECN240513 | |



2044- 2 X xx G xx R B -LCP

- Series
- Double Row
- No. of Pin Per Row
- G: Gold Plated
- T: Tin Plated
- LCP: Housing Material LCP
- A: Tray Package
- B: Bulk Package
- R: Right Angle
- 00: G/F
- 10: 10 μ "
- 15: 15 μ "
- 30: 30 μ "

Material and Plating:

Housing: LCP, UL94V-0 , BLACK.

Signal Contacts : Brass .

Gold Plated on Contact Area and Gold Flash on Solder Tail over Nickel 50 μ " Min .

Electrical Characteristics:

Current Rating: 2 AMP.

Dielectric Withstanding Voltage: AC 1000V for 1 minute.

Insulator Resistance: 1000M Ω min. at DC 500V.


Contact Resistance: 20m Ω max. at DC 100mA.

Operating Temperature: -55°C~+105°C .

***RoHS Compliant**

Insertion Depth: 2.55mm to 6.20mm.

| | |
|-----------|--------------------------------|
| Position | 4 Thru 80 |
| Dimension | |
| A | 2.54 X No. of Position /2+0.4 |
| B | 2.54 X No. of Position /2-2.54 |

| | | | | | | | | |
|------------------|------------|----------------|------------------------------|-----|--|--|--|--|
| Tolerances | Dwg. No. | 2044-D0000-033 | Title: | |  OUPIIN ELECTRONIC(KUNSHAN) CO., LTD. P/N: 2044-2XxxGxxRB-LCP SHEET 1/1 Ver. No. R2 | | | |
| x = ± 0.5 | Projection | | 2044 Series | | | | | |
| .x = ± 0.25 | Unit | mm | Scale | 1:1 | | | | |
| .xx = ± 0.15 | Drawn By | XS 05/14'24 | 2.54mmX2.54mm(0.100"X0.100") | | | | | |